



## Critical Usage Information

---

### ClearView Mineral Magnet

---

The following is only the basic usage directions. Refer to the actual product label for First Aid, Warnings and other statements of use.

#### DIRECTIONS

1. For pools with iron, copper, manganese, and other metals present in the water, apply CLEARVIEW "MINERAL MAGNET" over entire pool surface with filter system operating. For best results use 1 quart of CLEARVIEW "MINERAL MAGNET" per 10,000 gallons of water to remove stains, prevent plating, and restore water clarity.
2. Regular use of CLEARVIEW "MINERAL MAGNET" will keep the pool water clean and the pool shell in good condition. For stain prevention use 1 quart of CLEARVIEW "MINERAL MAGNET" per 20,000 gallons if test indicated metals above 3 ppm, use 3 ounces of CLEARVIEW "MINERAL MAGNET" per 10,000 gallons of water per week if pool has a tendency to show increasing metal content in water.
3. Do not add more than the recommended dosage of CLEARVIEW "MINERAL MAGNET". For best results use early afternoon or evening when water temperatures are above 60 degrees F., and run pump for 24 hours.
4. Once dissolved, metal are transported to the filter where they can be removed by backwashing or filter cleaning.
5. For best results pool pH should be at 7.5 or above when treatment begins.
6. For copper / silver or ion treated pools, remove electrodes or turn off ionizer for 5 days.
7. Some clouding may occur, as a result of using CLEARVIEW "MINERAL MAGNET". If this occurs, run pump until water appears clear; usually 7-10 days. Maintain filter<sup>L</sup> pressure at 8-10 PSI or at normal operating.